

## ALSANIT products maintenance instruction

For the production of ALSANIT products is used:

- HPL boards,
- Melamine Faced Chipboards,
- other boards, i.e. glass or SANDWICH,
- fittings (hinges, locks, supports, etc..) made of plastics or metals,
- powder coated steel sheets,
- anodized or powder coated aluminum profiles.

### Before starting the use

Before use, make sure that the products are correctly installed. In particular, it is important to ensure that they are properly leveled (in three planes). Before use, the door should also be adjusted to make it in line with adjacent elements and to make the gaps between the elements equal. All production markings should be removed (not applicable to the brand name of the product) and the products should be thoroughly cleaned. If the assembly has not been ordered in ALSANIT, the steps described above are on the customer's side.

### Cleaning

The surfaces of the products should be cleaned and maintained with delicate, non-aggressive washing and cleaning agents with a neutral PH. In order to remove the dirt, cover the cleaned surface with a washing and cleaning agent. Use a soft, dry cloth to wipe off the cleaning agent along with any dissolved dirt. Repeat if necessary. For daily care, we recommend product A1, which also removes fingerprints. For local application and removal of extremely difficult stains, including graffiti, we recommend using the A2 preparation by ALSANIT.

### Daily maintenance of construction

All fixings such as screws and bolts must be visually inspected on a regular basis. Tighten any loose screws or bolts and other fixings immediately when loose. In the event of noticing a looseness of connections or deviation from the vertical of the structure, immediately take it out of service and perform adjustments.

### Daily maintenance of mechanic parts

All rotating elements must be visually inspected on a regular basis in order to verify their wear. Once noticed that the door stops automatically closing (applies to doors mounted on self-closing hinges) in a smooth manner or when there is a "squeaking" while door closing, remove it from the hinges and check if the lubricant on the pins has not been wiped off. Before lubricating the hinge, wipe off the remains of the old grease from the mating surfaces and lubricate them with a small amount of grease. It is recommended to lubricate the hinges quarterly.

Attention:

In self-closing hinges, too much grease may create an "air pillow" between the sleeve and the pin, which will prevent the door from closing automatically until it is removed.

### It is forbidden to :

1. Mechanical cleaning of the surface of plates and profiles with hard tools such as: spatulas, knives, scrapers and cleaning cloths, e.g. sandpaper, "steel brushes", etc.
2. Use of caustic agents, eg caustic soda, lysol, cleaning powders based on caustic soda, alkaline soda, in the form of powders, solvents, and acid-based cleaning agents.
3. Long-term action of a water stream on the surface of products.
4. Install paper containers and other items on walls and doors.

### Annual service inspections

Unless agreed otherwise, the condition for maintaining the warranty is ordering annual service inspections confirmed by the ALSANIT Service Report.

### Disclaimer

To avoid misconstruals, the buyer accepts that the binding version of the document is the one in Polish language version and the English version is for reference only.